

BIGLOADS

HOW TO LOAD A BOAT TRAILER

Quick renter reference - conventional boat trailer

LOAD POSITION - QUICK VISUAL



1 MATCH BOAT AND TRAILER

Confirm the trailer is rated and adjusted for the boat including fuel, batteries, gear, and accessories.

2 SET THE BOW CORRECTLY

Bring the bow snug to the bow stop/winch post as designed. Keep the hull centered on bunks or rollers.

3 USE BOW AND STERN STRAPS

Use the winch strap plus an independent bow safety connection where equipped, and secure the stern with rated transom straps.

4 CHECK BEFORE THE ROAD

Raise/secure the motor as required, remove loose gear, connect lights, and verify tires, bearings, coupler, and safety chains.

THIS TRAILER GVWR: _____ Payload: _____ Max boat wt.: _____ Owner phone: _____

STOP - BEFORE YOU TOW

- | | |
|--|--|
| ☒ Bow seated correctly | ☒ Transom straps secure |
| ☒ Winch strap secure | ☒ Motor/support secured |
| ☒ Bow safety secured | ☒ Lights/chain connected |

General renter reference only. Follow the trailer manufacturer labels/manual, tow vehicle limits, hitch ratings, tire ratings, and all applicable load securement laws. Never exceed GVWR or GAWR. Boat trailer setup, tongue weight, bunks/rollers, and motor position vary substantially. Follow boat, motor, and trailer manufacturer instructions.